

HO-400 / HO-400R INDIRECT FIRED HEATER



INFORMATION SHEET

FEATURES

- **Versatile Fuel Options**
Diesel, Oil, or Kerosene Compatibility
- **Secure Containment**
110% Steel Secondary Containment
- **Durable Heat Exchanger**
Fully Welded 16 ga 304 Stainless Steel
- **Robust Body Panels**
16 ga Carbon Steel with Chip-Resistant Coating
- **Reliable Mobility**
Flat-Free Tires with Reinforced Hubs
- **Flexible Fuel Capacity**
Optional 60 or 118 US gal (227 or 447 l) fuel tanks
- **High-Quality Burner**
Equipped with Riello Burner



SPECIFICATIONS

	HO-400	HO-400R
BTUH	325,000 - 390,000 BTUH 95 - 114 kW	325,000 - 390,000 BTUH 95 - 114 kW
Air Movement	2,400 CFM 68 m ³ /min	3,500 CFM 99 m ³ /min
Weight	580 lbs 263 kg	600 lbs 272 kg
Dimensions	70" x 30" x 52" 178 x 76 x 132 cm	70" x 30" x 55" 178 x 76 x 140 cm
Power Supply	120 V / 15 A	120 V / 15 A
Current Draw	9 A	8 A
Ducting Capability	50' max 15 m max	100' max 30 m max
Recirculating	No	Up to 50' Up to 15 m
Certification	CSA / UL	CSA / UL
Fuel Tank Capacity	48 US gal 182 l	48 US gal 182 l
Run Time	16 hrs @ 3 gal / hr 16 hrs @ 11 l / hr	16 hrs @ 3 gal / hr 16 hrs @ 11 l / hr
Fan Power	3/4 hp 0.55 kW	1 hp 0.74 kW
Thermostat	Yes	Yes

Info@HeaterSales.ca | (AB) 780 979 0220 | (ON) 437 826 7300